

OCI UREUM

Ureum 46N granulair



EG-MESTSTOF

Totaal Amidestikstof (N)			46	%
Amidestikstof			46	%
Biureet		max.	1,2	%
Formaldehyde		max.	0,5	%
Water		ca.	0,5	%
Zeefanalyse				
Fractie	tussen 2,0 - 4,5 mm	min.	90	%
Stortdichtheid ongetrild		ca.	750 kg/m³	

Opmerkingen

- OCI Agro behoudt zich het recht voor tussentijdse wijzigingen aan te brengen in de eigenschappen en specificaties van de vermelde producten.
- Overige documentatie (zoals safety data sheets en opslag & handling informatie kunt u vinden op de website van OCI Agro (www.oci-agro.com).

OCI AGRO

Mijnweg 1, 6167 AC Geleen
 P.O. Box 601, 6160 AP Geleen
 The Netherlands
 T +31 46 7020203
 F +31 46 4528615
 E info.agro@ocinitrogen.com

All data, suggestions and information given herein is deemed to be accurate and reliable, but is presented without warranty (expressed or implied) whatsoever. OCI Nitrogen B.V. does not accept any liability in connection with this information or use. It is the responsibility of each user to determine whether the information in this document is appropriate/suitable for their particular use, application or processing. Nothing in this document shall be deemed to alter or waive any provision of OCI Nitrogen's General Conditions of Sale or this disclaimer.

15.12.2018